

SX4+ Race Fuel

Safety Data Sheet

SX4+ Race Fuel

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : SX4+

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel

1.3. Details of the supplier of the safety data sheet

Valor, LLC/DBA Renegade
1200 Alsop Lane
Owensboro, KY 42303
T 270-683-2461

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 1	H224
Flam. Liq. 2	H225
Skin Irrit. 2	H315
Germ Cell Muta 2	H341
Carc. 1	H350
Repr. 2	H361
STOT SE 3	H335
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Hazard statements (GHS-US) :

Danger
H224 – Extremely flammable liquid and vapor
H225 – Highly flammable Liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H335 – May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H341 – Suspected of causing genetic defects
H350 – May cause cancer
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting/equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 – Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash thoroughly after handling

SX4+ Race Fuel

Safety Data Sheet

P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P308+P313 - If exposed or concerned: get medical attention/advice
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P331 - If swallowed, do NOT induce vomiting
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use CO₂, dry chemical, foam (AFFF/ATC) or water spray for extinction
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

Repeated exposure may cause skin dryness or cracking

Toxic to aquatic life with long lasting effects

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Methyl Benzene (Component)	(CAS No) 108-88-3	16 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373
Isopropyl ether	(CAS No) 108-20-3	10 - 30	Flam. Liq. 2, H225 STOT SE 3, H336
1 - Hexene	(CAS No) 592-41-6	10 - 30	Flam. Liq. 2 H225 Asp. Tox 1, H304 STOT SE 3, H335 STOT SE 3, H336
2-Methyl-1,3-butadiene	(CAS No) 78-79-5	422 - 48	Flam Liq. 1, H224 Germ Cell Mut. 2, H341 Carcin. 1, H350

SX4+ Race Fuel

Safety Data Sheet

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air. If not breathing, Do not use mouth to mouth method if victim ingested or inhaled the substance; give artificial respirations with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical advice. Get immediate medical attention.
- First-aid measures after skin contact : After contact with skin, wash immediately with plenty of water and soap. If skin reddening or irritation develops, seek medical attention.
- First-aid measures after eye contact : Immediately flush the eyes with plenty of water for at least 15 minutes while holding eyelids apart to ensure flushing of the entire surface of the eye. Continue flushing for an additional 15 minutes if a physician is not immediately available. Seek medical attention, preferably an ophthalmologist, immediately.
- First-aid measures after ingestion : If the material is swallowed, get immediate medical attention or advice. DO NOT induce vomiting unless directed to do so by medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Breathing high concentrations may be harmful. May cause central nervous system depression or effects. Symptoms may include headache, excitation, euphoria, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death, depending on the concentration and duration of exposure. Breathing high concentrations of this material, for example, in a confined space or by intentional abuse, can cause irregular heartbeats which can cause death.
- Symptoms/injuries after skin contact : Contact may cause reddening, itching and inflammation.
- Symptoms/injuries after eye contact : Contact may cause pain and severe reddening and inflammation of the conjunctiva. Effects may become more serious with repeated or prolonged contact.
- Symptoms/injuries after ingestion : May cause irritation of the mouth, throat and gastrointestinal tract. May cause central nervous system depression or effects. Symptoms may include salivation, pain, nausea, vomiting and diarrhea. Exposure may also cause central nervous system symptoms similar to those listed under "Inhalation"

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : CO₂, dry chemical, foam (AFFF/ATC) or water spray, dry sand, alcohol-resistant foam
- Unsuitable extinguishing media : Water may be ineffective

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable liquid and vapor.
- Hazardous Combustion Products : Carbon Monoxide (CO) Carbon dioxide (CO₂)
- Explosion hazard : In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Vapors may travel long distances along ground before igniting/flashing back to vapor source.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Use personal protection equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulate in low areas

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment. Do not flush into surface water or sanitary sewer system.

SX4+ Race Fuel

Safety Data Sheet

6.3. Methods and material for containment and cleaning up

- For containment : If possible, stop flow of product.
- Methods for cleaning up : Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillage into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Avoid skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water. Smoking, eating and drinking should be prohibited in the application area.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3. Specific end use(s)

Fuel

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl Benzene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

1 – Hexene (592-41-6)		
ACGIH TLV	ACGIH TWA (ppm)	50 ppm

Isopropyl ether (108-20-3)			
ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
TWA: 250 ppm	(Vacated) TWA: 500 ppm	IDLH: 1400 ppm	TWA: 250 ppm
STEL: 310 ppm	(Vacated) TWA: 2100 mg/m ³	TWA: 500 ppm	TWA: 1050 mg/m ³
	TWA: 500 ppm	TWA: 2100 mg/m ³	STEL: 310 ppm
	TWA: 2100 mg/m ³		STEL: 1320 mg/m ³

SX4+ Race Fuel

Safety Data Sheet

8.2. Exposure controls

Appropriate engineering controls	: Local exhaust and general ventilation must be adequate to meet exposure standards. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation locations
Hand protection	: Wear impervious gloves to minimize skin contact. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough
Eye protection	: Safety glasses. Wear splash goggles if splashing is likely. Eye wash bottle with pure water.
Skin and body protection	: Wear suitable working clothes. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
Respiratory protection	: If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Odor	: Strong hydrocarbon
Odor threshold	: No data available
pH	: Neutral
Relative evaporation rate (butylacetate=1)	: No data available
Initial Boiling point	: < 150°F
Flash point	: No data available
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available

Relative vapor density at 20 °C	: 9.05
Specific gravity	: .730
Solubility	: Negligible.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 100 %
-------------	---------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions. Sensitivity to light. Air sensitive. Heat Sensitive.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Heat, flames, and other ignition sources.

SX4+ Race Fuel

Safety Data Sheet

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful in contact with skin. Harmful if inhaled.

Isopropyl ether (108-20-3)	
LD50 oral rat	4700 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	Not listed

Methyl Benzene (108-88-3)	
LD50 oral rat	636 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
ATE US (oral)	636.00000000 mg/kg
ATE US (dermal)	8390.0

1-Hexene (592-41-6)	
LD50 oral rat	>5600 mg/kg
LC50 inhalation rat	32000 ppm /4h
LD50 Dermal rabbit	>2000 mg/kg

2-Methyl-1,3-butadiene (78-79-5)	
LD50 Oral	2043-2210 mg/kg (Rat)
LD50 Dermal	>1 mL/kg (Rat)
LC50 Vapor	180 mg/L (Rat) 4 h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : May cause eye irritation
Respiratory or skin sensitization : May cause respiratory tract irritation
Germ cell mutagenicity : Animal experiments showed mutagenic and teratogenic effects.
Carcinogenicity : May cause cancer.

Isopropyl ether (108-20-3)	
IARC	Not listed
NTP	Not listed
ACGIH	Not listed
OSHA	Not listed
Mexico	Not listed

Methyl Benzene (108-88-3)	
IARC group	3 - Not classifiable

1-Hexene (592-41-6)	
IARC	Not listed
NTP	Not listed
ACGIH	Not listed
OSHA	Not listed
Mexico	Not listed

2-Methyl-1,3-butadiene (78-79-5)	
IARC	Group 2B

SX4+ Race Fuel

Safety Data Sheet

NTP	Reasonably Anticipated
ACGIH	Not Listed
OSHA	X
Mexico	Not Listed

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness. Central nervous system (CNS)

Specific target organ toxicity (repeated exposure): May cause damage to organs through prolonged or repeated exposure. Affected organs include: blood, kidneys, reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms / effects, both acute and delayed : Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Other Adverse Effects : The toxicological properties have not been fully investigated.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Isopropyl ether (108-20-3)	
LC50 fish	91.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish	7000 mg/l (Exposure time: 96 h Static – Species: Lepomis macrochirus)
EC50 microtox	500 mg/L 5 min
EC50 water flea	190 mg/L, 48 h (daphnia magna)

Methyl Benzene (108-88-3)	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	> 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 2	12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])

1-Hexene (592-41-6)	
EC50 Freshwater Algae	>1000 mg/L, 96 h (pseudokirchneriella subcapitata)
LC50 Freshwater fish	5.6 mg/L, 96 h (rainbow trout)
EC50 Water Flea	=30 mg/L, 48 h Static (Daphnia magna) =230 mg/L, 48 h (Daphnia magna)
Microtox	Not listed

2-Methyl-1,3-butadiene (78-79-5)	
EC50 Freshwater Algae	>1000 mg/L, 96h (Scenedesmus quadricauda)
LC50 Fish	32.5 – 50.15 mg/L, 96 h static (Lepomis macrochirus)
LC50 Fish	58.75-95.32 mg/L, 96 h static (Pimephales promelas)
LC50 Fish	188.77 – 305.14 mg/L, 96h static (Poecilia reticulata)
Microtox	Not listed
EC50 Water Fleas	140 mg/L, 48 h (Daphnia magna)

SX4+ Race Fuel

Safety Data Sheet

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Isopropyl ether (108-20-3)	
Log Pow	1.52
2-Methyl-1,3-butadiene (78-79-5)	
Log Pow	2.42
Methyl Benzene (108-88-3)	
Log Pow	2.65
1-Hexene (592-41-6)	
Log Pow	3.39

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects


No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional and national hazardous waste regulations to ensure complete and accurate classification.
- Product : The products should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
- Contaminated Packaging : Empty Remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on the empty drum.

SECTION 14: Transport information

- In accordance with DOT
- Transport document description : UN1203 Gasoline includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol, 3, II
- UN-No.(DOT) : 1203
- DOT NA no. : UN1203
- DOT Proper Shipping Name : Gasoline
includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol
- Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid
- 
- Packing group (DOT) : II - Medium Danger

SX4+ Race Fuel

Safety Data Sheet

DOT Special Provisions (49 CFR 172.102)	: 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter. 177 - Gasoline, or, ethanol and gasoline mixtures, for use in internal combustion engines (e.g., in automobiles, stationary engines and other engines) must be assigned to Packing Group II regardless of variations in volatility. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B33 - MC 300, MC 301, MC 302, MC 303, MC 305, MC 306, and DOT 406 cargo tanks equipped with a 1 psig normal vent used to transport gasoline must conform to Table I of this Special Provision. Based on the volatility class determined by using ASTM D 439 and the Reid vapor pressure (RVP) of the particular gasoline, the maximum lading pressure and maximum ambient temperature permitted during the loading of gasoline may not exceed that listed in Table I. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal 178.275(d)(3)
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

SECTION 15: Regulatory information

15.1. US Federal regulations

Isopropyl ether (108-20-3)	
TSCA 12(b)	Not Applicable
SARA 313	Not Applicable
CWA (Clean Water Act)	Not Applicable
Clean Air Act	Not Applicable
CERCLA	Not Applicable
OSHA	Not Applicable
SARA 311/312 Hazards	See section 2 for more information
California Proposition 65	This product does not contain any Proposition 65 chemicals
Methyl Benzene (108-88-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
Methyl Benzene (108-88-3)	
SARA Section 313 - Emission Reporting	1.0 %
1-Hexene (592-41-6)	
TSCA 12(b)	Not Applicable
SARA 313	Not Applicable
CWA (Clean Water Act)	Not Applicable
Clean Air Act	Not Applicable
CERCLA	Not Applicable
SARA 311/312 Hazards	See section 2 for more information
California Proposition 65	This product does not contain any Proposition 65 Chemicals

SX4+ Race Fuel

Safety Data Sheet

2-Methyl-1,3-butadiene (78-79-5)	
TSCA	X
TSCA Inventory notification Active/Inactive	Active
TSCA – EPA Regulatory Flags	-
SARA 313	Weight% ≥15% SARA 313 Threshold Values % - .01
SARA 311/312 Hazard Categories	See Section 2 for more information
CWA (Clean water Act)	CWA – Hazardous Substances – x CWA Reportable Quantities – 100lb
CERCLA	This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)
California Proposition 65	This product contains the following Proposition 65 Chemicals Carcinogen

15.2. US State regulations

Methyl Benzene (108-88-3)				
U.S. – California - Proposition 65 - Carcinogens List	U.S. – California - Proposition 65 - Developmental Toxicity	U.S. – California - Proposition 65 - Reproductive Toxicity - Female	U.S. – California - Proposition 65 - Reproductive Toxicity – Male	No significance risk level (NSRL)
	Yes	Yes		

Isopropyl ether (108-20-3)
U.S. - Massachusetts - Right To Know List U.S. – Rhode Island – Right to Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

2-Methyl-1,3-butadiene (78-79-5)
U.S. - Massachusetts - Right To Know List U.S. - Illinois – Right to Know list U.S. – Rhode Island – Right to Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Methyl Benzene (108-88-3)
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

1-Hexene (592-41-6)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) Lists

2-Methyl-1,3-butadiene (78-79-5)	
US Department of Homeland Security	DHS Chemical Facility Anti-Terrorism Standard Release STQs – 10000lb

SX4+ Race Fuel

Safety Data Sheet

SECTION 16: Other information

Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 1	Flammable Liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Germ Cell Muta 2	Germ Cell Mutagenicity Category 2
Canc 1	Carcinogenicity Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H224	Extremely Flammable liquid and vapor
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

Trade Secret Provision: *In accordance with OSHA regulations and policies, the specific percentages and specific names of certain chemicals are being designated a trade secret and are not disclosed herein. In compliance with current regulations, this SDS provides the necessary properties and effects of the chemicals listed for this product. In cases of medical emergency, medical personnel can contact the emergency number listed and obtain the specifics of these chemicals. Should this need arise, we will request the attending physician provide to us, at such time as appropriate, a letter stating the medical necessity and a signature of confidentiality for the obtained information.*