

# Leaded Race Fuel

## Safety Data Sheet

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Leaded Race Fuel  
Product code : 9950

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel

#### 1.3. Details of the supplier of the safety data sheet

Valor, LLC/DBA Renegade  
1200 Alsop Lane  
Owensboro, KY 42303  
T 270-683-2461

#### 1.4. Emergency telephone number

No additional information available

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Liq. 1	H224
Acute Tox. 4 (Dermal)	H312
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Muta. 1B	H340
Carc. 1A	H350
Repr. 2	H361
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H224 - Extremely flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H312+H332 - Harmful in contact with skin or if inhaled  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H340 - May cause genetic defects  
H350 - May cause cancer  
H361 - Suspected of damaging fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical/ventilating/lighting/equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray

# Leaded Race Fuel

## Safety Data Sheet

P264 - Wash thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing  
P308+P313 - IF exposed or concerned: Get medical advice/attention  
P312 - Call a POISON CENTER/doctor/physician if you feel unwell  
P314 - Get medical advice and attention if you feel unwell  
P331 - If swallowed, do NOT induce vomiting  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P362 - Take off contaminated clothing and wash before reuse  
P370+P378 - In case of fire: Use CO2, dry chemical, foam (AFFF/ATC) or water spray for extinction  
P391 - Collect spillage  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Naphtha, petroleum, full-range alkylate, butane-containing	(CAS No) 68527-27-5	60 - 80	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Methyl tert-butyl ether	(CAS No) 1634-04-4	0 - 30	Flam. Liq. 2, H225
Diisopropyl ether	(CAS No) 108-20-3	0 - 30	Not classified
Toluene (Component)	(CAS No) 108-88-3	5 - 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	0 - 20	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Ethyl alcohol (Component)	(CAS No) 64-17-5	0 - 15	Flam. Liq. 2, H225 Carc. 1A, H350
Isopentane	(CAS No) 78-78-4	5 - 10	Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304
Tetraethyllead	(CAS No) 78-00-2	< 0.01	Flam. Liq. 4, H227 Acute Tox. 2 (Oral), H300 Acute Tox. 1 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 Repr. 1A, H360 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,2-Dichloroethane	(CAS No) 107-06-2	< 0.01	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 1B, H350 STOT SE 3, H335

# Leaded Race Fuel

## Safety Data Sheet

Name	Product identifier	%	Classification (GHS-US)
1,2-Dibromoethane	(CAS No) 106-93-4	< 0.01	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 1B, H350 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Kerosine, petroleum	(CAS No) 8008-20-6	< 0.01	Asp. Tox. 1, H304

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air. If not breathing, administer CPR or artificial respiration. Get immediate medical attention.
- First-aid measures after skin contact : After contact with skin, wash immediately with plenty of water and soap. If skin reddening or irritation develops, seek medical attention.
- First-aid measures after eye contact : Immediately flush the eyes with plenty of water for at least 15 minutes while holding eyelids apart to ensure flushing of the entire surface of the eye. Continue flushing for an additional 15 minutes if a physician is not immediately available. Seek medical attention, preferably an ophthalmologist, immediately.
- First-aid measures after ingestion : If the material is swallowed, get immediate medical attention or advice. DO NOT induce vomiting unless directed to do so by medical personnel.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Breathing high concentrations may be harmful. May cause central nervous system depression or effects. Symptoms may include headache, excitation, euphoria, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death, depending on the concentration and duration of exposure. Breathing high concentrations of this material, for example, in a confined space or by intentional abuse, can cause irregular heartbeats which can cause death.
- Symptoms/injuries after skin contact : Contact may cause reddening, itching and inflammation.
- Symptoms/injuries after eye contact : Contact may cause pain and severe reddening and inflammation of the conjunctiva. Effects may become more serious with repeated or prolonged contact.
- Symptoms/injuries after ingestion : May cause irritation of the mouth, throat and gastrointestinal tract. May cause central nervous system depression or effects. Symptoms may include salivation, pain, nausea, vomiting and diarrhea. Exposure may also cause central nervous system symptoms similar to those listed under "Inhalation"

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : CO2, dry chemical, foam (AFFF/ATC) or water spray
- Unsuitable extinguishing media : None.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable liquid and vapor.
- Explosion hazard : In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Vapors may travel long distances along ground before igniting/flashing back to vapor source.

#### 5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

# Leaded Race Fuel

## Safety Data Sheet

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : If possible, stop flow of product.  
Methods for cleaning up : Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillage into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Avoid skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### 7.3. Specific end use(s)

Fuel

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Methyl tert-butyl ether (1634-04-4)

USA ACGIH	ACGIH TWA (ppm)	50 ppm
-----------	-----------------	--------

#### Diisopropyl ether (108-20-3)

USA ACGIH	ACGIH TWA (ppm)	250 ppm
USA ACGIH	ACGIH STEL (ppm)	310 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2100 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm

#### Toluene (108-88-3)

USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

#### Xylenes (o-, m-, p- isomers) (1330-20-7)

USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm

# Leaded Race Fuel

## Safety Data Sheet

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>		
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
<b>Ethyl alcohol (64-17-5)</b>		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
<b>Isopentane (78-78-4)</b>		
USA ACGIH	ACGIH TWA (ppm)	600 ppm
<b>Tetraethyllead (78-00-2)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.075 mg/m <sup>3</sup>
<b>1,2-Dichloroethane (107-06-2)</b>		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	100 ppm
<b>1,2-Dibromoethane (106-93-4)</b>		
USA OSHA	OSHA PEL (TWA) (ppm)	20 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	30 ppm
<b>Kerosine, petroleum (8008-20-6)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures)

### 8.2. Exposure controls

Appropriate engineering controls	: Local exhaust and general ventilation must be adequate to meet exposure standards.
Hand protection	: Wear impervious gloves to minimize skin contact.
Eye protection	: Safety glasses. Wear splash goggles if splashing is likely.
Skin and body protection	: Wear suitable working clothes.
Respiratory protection	: If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Clear
Odor	: Strong hydrocarbon
Odor threshold	: No data available
pH	: Neutral
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 90 - 437 °F
Flash point	: -50 °F
Self ignition temperature	: 495 °F
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available

# Leaded Race Fuel

## Safety Data Sheet

Relative vapor density at 20 °C	: 3 - 4
Specific gravity	: 5.9 - 6.3 lb/gal
Solubility	: Negligible.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 1.4 - 7.6 vol %

### 9.2. Other information

VOC content	: 100 %
-------------	---------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

### 10.3. Possibility of hazardous reactions

Will not occur.

### 10.4. Conditions to avoid

Heat, flames, and other ignition sources.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful in contact with skin. Harmful if inhaled.

Leaded Race Fuel	
ATE US (dermal)	1100.00000000 mg/kg body weight
ATE US (gases)	4500.00000000 ppmV/4h
ATE US (vapors)	11.00000000 mg/l/4h
ATE US (dust, mist)	1.50000000 mg/l/4h

Naphtha, petroleum, full-range alkylate, butane-containing (68527-27-5)	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h

Methyl tert-butyl ether (1634-04-4)	
LD50 oral rat	4 g/kg
LD50 dermal rabbit	> 10000 mg/kg
LC50 inhalation rat (ppm)	23576 ppm/4h
ATE US (oral)	4000000.00000000 mg/kg

Diisopropyl ether (108-20-3)	
LD50 oral rat	4700 mg/kg
LD50 dermal rabbit	20 ml/kg
ATE US (oral)	4700.00000000 mg/kg
ATE US (dermal)	20000.00000000 mg/kg

# Leaded Race Fuel

## Safety Data Sheet

<b>Toluene (108-88-3)</b>	
LD50 oral rat	636 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
ATE US (oral)	636.00000000 mg/kg
ATE US (dermal)	8390.00000000 mg/kg

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 oral rat	4300 mg/kg
LC50 inhalation rat (mg/l)	47635 mg/l/4h
ATE US (oral)	4300.00000000 mg/kg
ATE US (dermal)	1100.00000000 mg/kg

<b>Ethyl alcohol (64-17-5)</b>	
LC50 inhalation rat (mg/l)	124.7 mg/l/4h
ATE US (oral)	7060.00000000 mg/kg

<b>Tetraethyllead (78-00-2)</b>	
LC50 inhalation rat (mg/l)	850 mg/m <sup>3</sup> (Exposure time: 1 h)
ATE US (oral)	5.00000000 mg/kg body weight
ATE US (dermal)	5.00000000 mg/kg body weight
ATE US (gases)	100.00000000 ppmV/4h
ATE US (vapors)	0.50000000 mg/l/4h
ATE US (dust, mist)	0.05000000 mg/l/4h

<b>1,2-Dichloroethane (107-06-2)</b>	
LD50 oral rat	625 mg/kg
LD50 dermal rabbit	2800 mg/kg
LC50 inhalation rat (ppm)	1000 ppm (Exposure time: 7 h)
ATE US (oral)	625.00000000 mg/kg body weight
ATE US (dermal)	2800.00000000 mg/kg body weight
ATE US (gases)	700.00000000 ppmV/4h
ATE US (vapors)	3.00000000 mg/l/4h
ATE US (dust, mist)	0.50000000 mg/l/4h

<b>1,2-Dibromoethane (106-93-4)</b>	
LD50 oral rat	108 mg/kg
LD50 dermal rabbit	300 mg/kg
ATE US (oral)	108.00000000 mg/kg body weight
ATE US (dermal)	300.00000000 mg/kg body weight
ATE US (gases)	700.00000000 ppmV/4h
ATE US (vapors)	3.00000000 mg/l/4h
ATE US (dust, mist)	0.50000000 mg/l/4h

<b>Kerosine, petroleum (8008-20-6)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

<b>Methyl tert-butyl ether (1634-04-4)</b>	
IARC group	3 - Not classifiable

<b>Toluene (108-88-3)</b>	
IARC group	3 - Not classifiable

# Leaded Race Fuel

## Safety Data Sheet

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
IARC group	3 - Not classifiable
<b>Ethyl alcohol (64-17-5)</b>	
IARC group	1 - Carcinogenic to humans
<b>Tetraethyllead (78-00-2)</b>	
IARC group	3 - Not classifiable
<b>1,2-Dichloroethane (107-06-2)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
<b>1,2-Dibromoethane (106-93-4)</b>	
IARC group	2A - Probably carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure. Affected organs include: blood, kidneys, reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
Aspiration hazard	: May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

<b>Naphtha, petroleum, full-range alkylate, butane-containing (68527-27-5)</b>	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysisopsis bahia)
<b>Methyl tert-butyl ether (1634-04-4)</b>	
LC50 fish 1	672 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	542 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 800 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
LC50 fish 2	929 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 other aquatic organisms 2	184 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
<b>Diisopropyl ether (108-20-3)</b>	
LC50 fish 1	91.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	190 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	7000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
<b>Toluene (108-88-3)</b>	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	> 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 2	12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
<b>Ethyl alcohol (64-17-5)</b>	
LC50 fish 1	12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])



# Leaded Race Fuel

## Safety Data Sheet

<b>Ethyl alcohol (64-17-5)</b>	
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>Isopentane (78-78-4)</b>	
EC50 Daphnia 1	2.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Tetraethyllead (78-00-2)</b>	
LC50 fish 1	84 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
EC50 Daphnia 1	0.085 mg/l (Exposure time: 48 h - Species: Artemia salina)
LC50 fish 2	19.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
<b>1,2-Dichloroethane (107-06-2)</b>	
LC50 fish 1	110 - 123 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	140 - 190 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	225 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
<b>1,2-Dibromoethane (106-93-4)</b>	
LC50 fish 1	27.6 - 37.4 mg/l (Exposure time: 96 h - Species: Oryzias latipes [flow-through])

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>Methyl tert-butyl ether (1634-04-4)</b>	
BCF fish 1	(no bioaccumulation expected)
Log Pow	1.06 (at 23 °C)
<b>Diisopropyl ether (108-20-3)</b>	
Log Pow	1.52 (at 20 °C)
<b>Toluene (108-88-3)</b>	
Log Pow	2.65
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15
<b>Ethyl alcohol (64-17-5)</b>	
Log Pow	-0.32
<b>Isopentane (78-78-4)</b>	
Log Pow	3.2 - 3.3
<b>Tetraethyllead (78-00-2)</b>	
BCF fish 1	92 - 3189
Log Pow	4.32 (at 20 °C)
<b>1,2-Dichloroethane (107-06-2)</b>	
BCF fish 1	2
Log Pow	1.45
<b>1,2-Dibromoethane (106-93-4)</b>	
BCF fish 1	< 10
Log Pow	1.93

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

# Leaded Race Fuel

## Safety Data Sheet

### SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1203 Gasoline includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol, 3, II

UN-No.(DOT) : 1203

DOT NA no. : UN1203

DOT Proper Shipping Name : Gasoline  
includes gasoline mixed with ethyl alcohol, with not more than 10% alcohol

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter.  
177 - Gasoline, or, ethanol and gasoline mixtures, for use in internal combustion engines (e.g., in automobiles, stationary engines and other engines) must be assigned to Packing Group II regardless of variations in volatility.  
B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
B33 - MC 300, MC 301, MC 302, MC 303, MC 305, MC 306, and DOT 406 cargo tanks equipped with a 1 psig normal vent used to transport gasoline must conform to Table I of this Special Provision. Based on the volatility class determined by using ASTM D 439 and the Reid vapor pressure (RVP) of the particular gasoline, the maximum lading pressure and maximum ambient temperature permitted during the loading of gasoline may not exceed that listed in Table I.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Methyl tert-butyl ether (1634-04-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %

##### Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on SARA Section 313 (Specific toxic chemical listings)

# Leaded Race Fuel

## Safety Data Sheet

<b>Toluene (108-88-3)</b>	
SARA Section 313 - Emission Reporting	1.0 %
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1.0 %
<b>Tetraethyllead (78-00-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 302 (Specific toxic chemical listings)	
SARA Section 302 Threshold Planning Quantity (TPQ)	100
<b>1,2-Dichloroethane (107-06-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	0.1 %
<b>1,2-Dibromoethane (106-93-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	0.1 %

### 15.2. US State regulations

<b>Toluene (108-88-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes	Yes		
<b>Ethyl alcohol (64-17-5)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes			
<b>1,2-Dichloroethane (107-06-2)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
<b>1,2-Dibromoethane (106-93-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes		Yes	
<b>Methyl tert-butyl ether (1634-04-4)</b>				
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Diisopropyl ether (108-20-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List				

# Leaded Race Fuel

## Safety Data Sheet

### Diisopropyl ether (108-20-3)

U.S. - Pennsylvania - RTK (Right to Know) List

### Toluene (108-88-3)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Xylenes (o-, m-, p- isomers) (1330-20-7)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Ethyl alcohol (64-17-5)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Isopentane (78-78-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Tetraethyllead (78-00-2)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### 1,2-Dichloroethane (107-06-2)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### 1,2-Dibromoethane (106-93-4)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Kerosine, petroleum (8008-20-6)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 1 (Dermal)	Acute toxicity (dermal) Category 1
Acute Tox. 2 (Inhalation)	Acute toxicity (inhalation) Category 2
Acute Tox. 2 (Oral)	Acute toxicity (oral) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2

# Leaded Race Fuel

## Safety Data Sheet

Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 1A	Reproductive toxicity Category 1A
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H300	Fatal if swallowed
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H310	Fatal in contact with skin
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*